








































Eulumdata



Lightsources / Světelné zdroje

Symbol	Code	W	V	Socket	lm	lm/W	<mm>
	D45	60	230	E14	660	11	75
	A45	60	230	E27	660	11	75
	A60	60	230	E27	710	11,83	105
	T60 SOFT	75	230	E27	840	11	105
	A60	100	230	E27	1380	13,80	105
	SOFT GLOBE G80	60	230	E27	1000	10	
	SOFT GLOBE G95	60	230	E27	890	8,9	
	QT-DE12	100 150 150 300 500	230	R7s R7s R7s R7s R7s	1600 2500 2500 5000 9500	16 17 16 17 19	74,9 74,9 114,2 114,2 114,2
	ES 63	75	230	GU10			62
	ES 50	50	230	GU10			55
	ESD 50	50	230	GZ10			55
	QR-CBC51	20 35 50	12	GU5,3 GU5,3 GU5,3			45 45 45
	QT9-ax	50	230	G4			45
	HALOGEN	25 40	230	G9 G9	260 490	10,4 12,25	43 43
	TC-SL	5		2G7	250	69	85
	TC	9		G23	600	67	167
	TC-L	18 24 36 55		2G11 2G11 2G11 2G11	1200 1800 2900 4800	67 75 80 87	217 320 415 535
	TC-TSE	15 23	230	E27 E27	900 1500	60 66	

Symbol	Code	W	V	Socket	lm	lm/W	<mm>
	TC-D	10		G24d-1	600	60	110
		13		G24d-1	900	69	138
		26		G24d-3	1800	69	172
	TC-DEL	10		G24q-1	600	60	103
		13		G24q-1	900	69	131
		26		G24q-3	1800	69	165
	TC-T	26		Gx24d-3	1800	69	133
	TC-TEL	26		Gx24q-3	2400	69	133
		32		Gx24q-3	2400	75	142
		42		Gx24q-4	2400	76	163
	TC-F	36		2G10	2800	78	217
	T2	8		W 4,3x8,5d	540	68	320
	T2	11		W 4,3x8,5d	750	68	421
	T2	13		W 4,3x8,5d	930	72	523
	T5	8		G5	450	86	288
	T5	14		G5	1200	86	549
	T5	21		G5	1900	91	849
	T5	28		G5	2600	93	1149
	T5	35		G5	3300	95	1449
	T5	24		G5	1750	73	549
	T5	39		G5	3100	80	849
	T5	49		G5	4300	88	1449
	T5	54		G5	4450	83	1149
	T5	80		G5	6150	77	1449
	T8	15		G13	950	63	438
	T8	18		G13	1350	75	590
T8	30		G13	2400	80	895	
T8	36		G13	3350	93	1200	
T8	58		G13	5200	90	1500	
	TL-5C	22		2xG13	1800	81,81	225
	TL-5C	40		2xG13	3200	80	300

Lightsource's Colour / Barva světelného zdroje

827 / 2700 °K

830 / 3000 °K

840 / 4000 °K